

MATERIAL SAFETY DATA SHEET - COMPLIES WITH 29 CFR 1910-1200

FORMAT PN/GP

***** SECTION I *****

DATE PRINTED-09/01/04 REVISED-08/09/04

PPG TrueFinish
 PPG Industries
 Pittsburgh, PA 15272
 MANUFACTURERS NAME: CUSTOM-PAK PRODUCTS, INC.
 INFORMATION TELEPHONE: (262) 251-6180

MANUFACTURERS CODE I.D.: 38L025M-0.3
 PRODUCT CLASS: PAINT PEN, 1/3 OZ.
 PRODUCT DESC: LIFE FITNESS
 Q1356P9001

HMIS INFORMATION:
 HEALTH.....2
 FLAMMABILITY...3
 REACTIVITY....1
 PROTECTIVE EQ..

24 HR TRANSPORTATION EMERGENCY TELEPHONE: 1-800-688-4005
 FOR EMERGENCY TRANSPORTATION ISSUES REFERENCE 38L025M-0.3

ARCTIC SILVER

SPECIAL LABEL REQUIRED PP183
 FRONT AND BACK PANEL

***** SECTION II - HAZARDOUS INGREDIENTS *****

INGREDIENT	CAS #	VOLATILE		VAPOR PRESSURE		OSHA	ACGIH	SARA 313	LISTED CARCINOGEN		
		%	LEL	mm Hg.	@20C	PEL-PPM	TLV-PPM	LISTED	NTP	IARC	OSHA
		BY WEIGHT									
GLYCOL ETHER EB	111-76-2	20-26	1.1	0.88		25	25	Y	N	N	N
N-BUTYL ACETATE	123-86-4	10-16	1.7	6.30		150	150	N	N	N	N
ETHYL ACETATE	141-78-6	10-16	2.2	29.30		400	400	N	N	N	N
ISOBUTYL ACETATE	110-19-0	10-16	1.4	13.0		150	150	N	N	N	N
ISOPROPYL ALCOHOL	67-63-0	8-10	2.0	33.0		400	400	N	N	N	N
NITROCELLULOSE RESIN	9004-70-0	5-8	N/A	N/A		N/A	N/A	N	N	N	N
METHYL ETHYL KETONE	78-93-3	3-5	1.8	83.0		200	200	Y	N	N	N
XYLENE	1330-20-7	3-5	1.0	5.1		100	100	Y	N	N	N
N-BUTYL ALCOHOL	71-36-3	3-5	1.4	4.4		50	50	Y	N	N	N
*ETHYLBENZENE	100-41-4	.01-1	1.0	7.1		100	100	Y	N	Y	N

* SEE WARNING SECTION V

***** SECTION III - PHYSICAL DATA *****

BOILING RANGE: 175F to 340F % VOLATILE BY VOLUME: 80.78 VAPOR DENSITY: Heavier than Air APPEARANCE: Opaque Liquid
 WEIGHT PER GALLON: 7.814 WATER SOLUABILITY: Negligible ODOR: Solvent Odor EVAPORATION RATE: Slower than Ether

*****SECTION IV - FIRE AND EXPLOSION HAZARD DATA *****

DOT PROPER SHIPPING NAME: CONSUMER COMMODITY ID NO.: UN1263 HAZARD CLASS: ORM-D-AIR
 PACKAGE GROUP: LABEL REQUIREMENT:

EXTINGUISHING MEDIA: Use (NFPA) CLASS B extinguisher, CO2 or foam. LEL: See Section II
 FLASH POINT: 35F

UNUSUAL FIRE AND EXPLOSION HAZARDS: Pressure build up due to heat exposure may cause containers to explode.
 Water may be used to cool ruptured containers.

SPECIAL FIRE FIGHTING PROCEDURES: Fight fire from safe distance. Wear full protective equipment,
 including self-contained breathing gear.

***** SECTION V - HEALTH HAZARD DATA *****

EFFECTS OF OVEREXPOSURE: (ACUTE) Anesthetic effect. Irritation of the respiratory tract or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness or coma. EYE....Contact may cause redness, irritation, tearing and blurred vision. SKIN....Contact may dry skin causing cracks and irritation. INGESTION.... May be harmful or fatal if swallowed.

(CHRONIC) Reports have associated repeated and prolonged occupation overexposure to solvents with liver, kidney, brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Asthma and other respiratory ailments. Chemical sensitization.

PRIMARY ROUTE(S) OF ENTRY: (X) DERMAL (X) INHALATION () INGESTION () ABSORPTION

EMERGENCY AND FIRST AID PROCEDURES: VAPORS....Remove from exposure. Administer oxygen if necessary. Call a physician. EYES....Immediately flush eyes with water for at least 15 minutes. Get medical attention. SKIN....Remove contaminated clothing and shoes. Wash contact area with soap and water. Wash clothing and shoes before reuse. INGESTION....Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult physician or Poison Control Center immediately.

* WARNING: This product contains an ingredient which has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain.

***** SECTION VI - REACTIVE DATA *****

STABILITY: STABLE (X) UNSTABLE (). HAZARDOUS POLYMERIZATION; MAY OCCUR () WILL NOT OCCUR (X)
CONDITIONS TO AVOID: High temperatures and open flames. INCOMPATIBLE MATERIALS TO AVOID: Unknown
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide. Carbon Monoxide.

***** SECTION VII - SPILL OR LEAK PROCEDURE *****

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED: Eliminate all ignition sources. Provide ventilation. Collect spills with absorbent materials and non-sparking tools. See Section VIII for protective equipment.
WASTE DISPOSAL METHOD: Dispose of in accordance with Federal, State and Local regulations. Do not incinerate containers.

***** SECTION VIII - SPECIAL PROTECTION INFORMATION/CONTROL MEASURES *****

RESPIRATORY PROTECTION: In open areas with unrestricted ventilation, an NIOSH/MSHA approved respirator to remove solid airborne particles of overspray may be used if prolonged and repeated exposure is likely. In areas with restricted ventilation the use of an approved chemical/mechanical filter designed to remove both particles and organic vapors is recommended.
VENTILATION: Supply sufficient ventilation to keep air contaminant concentration below current OSHA (PEL) or ACGIH (TLV).
PROTECTIVE GLOVES: Use protective gloves if contact with product is likely.
OTHER PROTECTIVE EQUIPMENT: Safety glasses to prevent eye contact.
HYGIENIC PRACTICES: Wash hands before eating or using washroom.

***** SECTION IX - SPECIAL PRECAUTIONS *****

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store in areas above 120F or near fire or open flame. When storing large quantities, storage conditions should comply with OSHA 1910.106. This product complies with the Toxic Substances Control Act (TSCA) 40 CFR 700-799 and the Canadian Dangerous Substance List (DSL).
OTHER PRECAUTIONS: Prevent prolonged or repeated breathing of vapor or spray mist. Do not take internally. Keep out of reach of children. Use with adequate ventilation.