

Isopropyl Alcohol

# Material Safety Data Sheet

## SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade name	Isopropyl Alcohol	
Synonyms	Dimethyl carbinol, Isopropanol	
Manufacturer/Supplier	SASOL CHEMICALS NORTH AMERICA LLC (An affiliate of Sasol North America Inc.)	
Address	900 Threadneedle, Houston, TX 77079	
Telephone	CHEMTREC North America Transportation Emergency (24-hr)	(800) 424-9300
	CHEMTREC World Wide	(703) 527-3887
	Other Emergencies (24-hr)	(337) 494-5142
	MSDS and Product Information (8:00am-4:30pm CST)	(281) 588-3491
	Health and Safety Information (8:00am-4:00pm CST)	(281) 588-3492

## SECTION 2 COMPOSITION AND INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS-No.</u>	<u>Weight %</u>
2-Propanol	67-63-0	100.0

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.


## SECTION 3 HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

Appearance	Colorless liquid
Odor	Aromatic. Pleasant resembling a mixture of ethanol and acetone. (slight)
Precautions	<b>WARNING! FLAMMABLE LIQUID AND VAPOR CAUSES EYE IRRITATION AND MAY CAUSE SKIN IRRITATION.</b> Keep away from heat and flame. Use only with adequate ventilation. Avoid contact with skin, eyes and clothing.
Environmental precautions	Do not flush into surface water or sanitary sewer system. Low toxicity to aquatic organisms such as bacteria, algae, protozoa and fish. Readily biodegradable.

### POTENTIAL HEALTH EFFECTS

**Eyes** Irritating to eyes. May cause corneal inflammation.



## Isopropyl Alcohol

- Skin** Repeated or prolonged contact can cause redness, irritation and scaling of the skin (dermatitis). Normal care and personal hygiene should prevent skin effects.
- Inhalation** Irritation of the nose and throat, dizziness, and headache.
- Ingestion** Depression of central nervous system can occur. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

(See Section 11 for Toxicological Information)


## SECTION 4 FIRST AID MEASURES

- Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
- Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.
- Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately.
- Ingestion** If swallowed, call a physician or poison control center immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

## SECTION 5 FIRE FIGHTING MEASURES

### FLAMMABLE PROPERTIES

- Flash point** 11.67 °C closed cup 53 °F 18.3 °C open cup 64.9 °F
- Autoignition temperature** 398.89 °C 750 °F
- Flammable limits in air % by volume** Lower explosion limit: 2 %(V)  
Upper explosion limit: 12 %(V)
- Fire and explosion** Vapours may form explosive mixture with air. Flash back possible over considerable distance. Use water spray to disperse the vapors. NFPA Class IB flammable liquid.
- Extinguishing media** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Fire fighting instructions** Self-contained breathing apparatus (SCBA) and structural firefighter's protective clothing will provide limited protection.
- Further information** Keep containers and surroundings cool with water spray. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.



## Isopropyl Alcohol

---

---

### SECTION 6 ACCIDENTAL RELEASE MEASURES

<b>Steps to be taken in case of spill or leak</b>	Evacuate personnel to safe areas. Remove all sources of ignition. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Do not flush into surface water or sanitary sewer system.
---	---

---

### SECTION 7 HANDLING AND STORAGE

<b>Electrostatic accumulation hazard</b>	Ensure all equipment is electrically grounded before beginning transfer operations.
<b>Storage/Transport pressure</b>	Ambient
<b>Further information on storage conditions</b>	Keep away from heat and sources of ignition.

---


### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### ENGINEERING MEASURES

Air contaminant levels should be controlled below the PEL or TLV for this product (see Exposure Guidelines). Mechanical ventilation may be necessary if working with this product in enclosed areas and/or at elevated temperatures. Use explosion-resistant equipment

#### PERSONAL PROTECTIVE EQUIPMENT

<b>Eyes</b>	When contact with liquid is possible, use a face shield and/or chemical splash goggles. Otherwise use safety glasses with side shields or goggles.
<b>Skin</b>	Wear suitable protective clothing, gloves and eye/face protection.
<b>Inhalation</b>	Respiratory protection is normally not required except in emergencies or when conditions cause excessive airborne levels of mists or vapors. NIOSH-approved organic vapor air-purifying respirator, self-contained breathing apparatus, or air-supplied respirators where there may be potential for overexposure.



## Isopropyl Alcohol

---

### EXPOSURE GUIDELINES

#### Components   Exposure limit(s)

**2-Propanol**   OSHA PEL 400 ppm (983 mg/m<sup>3</sup>)  
                       ACGIH TLV (8-hour) 400 ppm (983 mg/m<sup>3</sup>)  
                       ACGIH STEL (15-minute) 500 ppm (1,230 mg/m<sup>3</sup>)

PEL= Permissible Exposure Limits  
 TLV= Threshold Limit Value  
 EL= Excursion Limit

TWA= Time Weighted Average (8 hr.)  
 STEL= Short Term Exposure Limit (15 min.)  
 WEEL= Workplace Environmental Exposure Level

---

## SECTION 9   PHYSICAL AND CHEMICAL PROPERTIES

**Appearance**   liquid

**Colour**   Colorless

**Odour**   Aromatic. Pleasant resembling a mixture of ethanol and acetone. (slight)

**Form**   liquid

**Boiling point/range**   82.22 °C   180 °F

**Vapour pressure**   33 mm Hg   @ 20 °C

**Vapor density**   2.08

**Solubility (water)**   completely soluble

**Viscosity**   3.03 cSt

**Melting point/range**   -88.5 °C   -127.3 °F

**Specific gravity**   0.79 g/cm<sup>3</sup>


**pH**   7

**Evaporation rate**   2.88

---

## SECTION 10   STABILITY AND REACTIVITY

**Conditions to avoid**   Keep away from heat and sources of ignition.



## Isopropyl Alcohol

<b>Hazardous decomposition products</b>	Combustion products include carbon dioxide, carbon monoxide and possibly other unidentified organic compounds.
<b>Incompatibility with other materials</b>	Can react with strong oxidizers, inorganic acids, and halogens.
<b>Hazardous polymerization</b>	None

## SECTION 11 TOXICOLOGICAL INFORMATION

**Additional Remarks** Exposure can cause nausea, headache and vomiting. May be harmful by inhalation, ingestion, skin adsorption.

**Eyes** Irritating to eyes.

**Skin**  
Acute dermal LD50 (rabbit): 12,800 mg/kg

**Inhalation** Acute 4 hours LC50 (rat): 16,970 mg/l

**Ingestion** Acute oral LD50 (rat): 5,045 mg/kg

## CARCINOGENICITY

This product contains no carcinogenic substances.

## SECTION 12 ECOLOGICAL INFORMATION

**Aquatic toxicity** Low toxicity to aquatic organisms such as bacteria, algae, protozoa and fish.  
LC50 (Leuciscus idus melanotus) 48 hours > 100 mg/l  
LC50 (Brown shrimp) 96 hours 467,923 mg/l  
EC50 (Brine shrimp) 48 hours > 100 mg/l



## Isopropyl Alcohol

---

EC50 (S. subspicatus (algae)): > 100 mg/l

Biodegradation 72 hours  
Readily biodegradable.

---

## SECTION 13 DISPOSAL CONSIDERATIONS

- Waste code** D001 - Ignitability (RQ 100 LB) This product has the RCRA characteristic of ignitability. Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification.
- Disposal methods** Dispose of only in accordance with local, state, and federal regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.
- Empty containers** Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

---

## SECTION 14 TRANSPORT INFORMATION

- DOT description** Isopropanol, 3, UN 1219, II  
This product is regulated as a hazardous material as defined by the Department of Transportation (DOT).
- IATA description** Isopropanol, 3, UN 1219, II  
This product is regulated as a dangerous good as defined by ICAO/IATA for air transportation.
- IMDG description** Isopropanol, 3, UN 1219, II  
This product is regulated as a dangerous good as defined by the IMDG Code for marine transport.



## Isopropyl Alcohol

### SECTION 15 REGULATORY INFORMATION

#### U.S. FEDERAL REGULATIONS

##### OSHA classification

Flammable liquid and eye irritant

##### TSCA Inventory Listing

###### Components

###### CAS-No.

2-Propanol

67-63-0

##### SARA 302 Status

###### Components

###### CAS-No.

###### Weight %

Contains no chemicals subject to SARA 302 reporting.

##### SARA 311/312 Classification

"Fire hazard", "Immediate (acute) health hazard"

##### SARA 313 Chemical

###### Components

###### CAS-No.

###### Weight %

2-Propanol

67-63-0

100.00

##### CERCLA Hazardous Substance

###### Components

###### CERCLA RQ

###### Weight %

Contains no chemicals subject to CERCLA.

#### INTERNATIONAL REGULATIONS

##### Workplace Hazardous Materials Information System (WHMIS) Classification


Class B, Division 2: Flammable liquid.

Class D, Division 2, Subdivision A: Very toxic material

Class D, Division 2, Subdivision B: Toxic material.

##### Australian Inventory of Chemical Substances (AICS) Listing

The components of this product are listed on the AICS.



## Isopropyl Alcohol

### Japanese Minister of International Trade and Industry (MITI) Inventory Listing

The components of this product are listed on the MITI.

### Canadian Domestic Substance List (DSL) Inventory Listing

The components of this product are listed on the DSL.

### European Inventory of Existing Commercial Chemical Substances (EINECS) Listing

The components of this product are listed on the EINECS listing.

### Phillipines Inventory List (PICCS)

The components of this product are listed on the PICCS.

### Korean Inventory List

The components of this product are listed on the ECL.

### China Inventory List

The components of this product are listed on the China inventory.

## STATE REGULATIONS

### California Safe Drinking Water Act (Prop 65) Listing Components

CAS-No.

Contains no chemical subject to California Prop 65.

## SECTION 16 OTHER INFORMATION

### HAZARD RATINGS

	Health	Flammability	Reactivity
<b>HMIS</b>	1	3	0
<b>NFPA</b>	1	3	0

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR SASOL NORTH AMERICA'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH SASOL NORTH AMERICA CONSIDERS ACCURATE AND RELIABLE, SASOL NORTH AMERICA MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.