Issued to . . . . . : Life Fitness
10600 W Belmont Ave

Franklin Park IL 60131

Attention: . . . . . : Material Safety Data Sheet Coordinator

The attached Material Safety Data Sheet relates potential hazards and recommended practices for safe handling of the product.

We urge you and your employees to review the entire MSDS prior to handling, use or disposal of the product.

You are required to keep this MSDS on file for reference by company employees or government regulatory officials.

If you resell or distribute this product, you must furnish a copy of the MSDS to your customer.

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:
PRODUCT CODE. . . . : 03980 660605 .6B
PRODUCT NAME . . . : WHITE SK50-P0007-0000
PRODUCT CLASS . . . : Touch-Up Bottle

MSDS PREPARATION DATE : 12/21/2011

MANUFACTURER IDENTIFICATION:
RAABE COMPANY
PO BOX 1090

MENOMONEE FALLS WI 53052-1090

CUSTOMER IDENTIFICATION:
Life Fitness
10600 W Belmont Ave

Franklin Park IL 60131

EMERGENCY TELEPHONE NUMBERS:
24 HOURS A DAY - CALL CHEMTREC : 800-424-9300
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887
8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

---

1 ETHYLBENZENE
CAS# 100-41-4
ETHYLBENZENE
PCT BY WT: .6100 VAPOR PRESSURE: 7.000 MMHG @ 68F LEL .80
EXPOSURE LIMIT:

ACGIH TLV-TWA	100 ppm
ACGIH TLV-STEL	125 ppm
OSHA PEL-TWA	100 ppm
OSHA PEL-STEL	125 ppm
OTHER	IARC (2B), CALIFORNIA PROP 65 (Cancer 6/11/2004)

LD50(ORAL)	3500 mg/kg (rat)
LD50(DERMAL)	20574 mg/kg (rabbit)
LC50	17623 mg/m3 (rat)

OTHER LIMITS:
PROP 65-Cancer,listed 6/11/04 EINECS 202-849-4

---

2 TITANIUM DIOXIDE
CAS# 13463-67-7
TITANIUM DIOXIDE
PCT BY WT: 16.0000
EXPOSURE LIMIT:

ACGIH TLV-TWA	10 mg/m3
ACGIH TLV-STEL	NO INFO
OSHA PEL-TWA	10 mg/m3
COMPANY	N.E.
LD50(ORAL)	> 24000 mg/kg (rat)
LC50	> 6820 mg/m3 (rat)

OTHER LIMITS:
EINECS 236-675-5

---

3 XYLENE
CAS# 1330-20-7
XYLENE
PCT BY WT: 3.0000 VAPOR PRESSURE: 6.600 MMHG @ 68F LEL 1.00
EXPOSURE LIMIT:

ACGIH TLV-TWA	100 ppm
ACGIH TLV-STEL	150 ppm
OSHA PEL-TWA	100 ppm
OSHA PEL-STEL	150 ppm
COMPANY	N.E.
LD50(ORAL)	4300 mg/kg (rat)
LD50(DERMAL)	1700 mg/kg (rabbit)
LC50	18892 mg/m3 (rat)

OTHER LIMITS:
EINECS 215-535-7

---

4 METHYL ETHYL KETONE
CAS# 78-93-3
METHYL ETHYL KETONE
PCT BY WT: 17.0000 VAPOR PRESSURE: 85.000 MMHG @ 68F LEL 1.80
EXPOSURE LIMIT:

ACGIH TLV-TWA	200 ppm
ACGIH TLV-STEL	300 ppm
OSHA PEL-TWA	200 ppm
COMPANY	N.E.
LD50(ORAL)	2737 mg/kg (rat)
LD50(DERMAL)	6480 mg/kg (rat)
LC50	23500 mg/m3 (rat)

OTHER LIMITS:
EINECS 201-159-0

---

5 GLYCOL ETHER PM ACETATE
CAS# 108-65-6
PROPYLENE GLYCOL METHYL ETHER ACETATE
PCT BY WT: 14.0000 VAPOR PRESSURE: 3.700 MMHG @ 68F LEL 1.30
EXPOSURE LIMIT:

ACGIH TLV-TWA	NOT ESTABLISHED
ACGIH TLV-STEL	NOT ESTABLISHED
LD50(ORAL)	8500 mg/kg (rat)
LD50(DERMAL)	5000 mg/kg (rat)
LC50	5321 mg/m3 (rat)

OTHER LIMITS:
EINECS 203-603-9

---

6 TOLUENE
CAS# 108-88-3
TOLUENE
PCT BY WT: 22.0000 VAPOR PRESSURE: 38.000 MMHG @ 68F LEL 1.40
EXPOSURE LIMIT:

ACGIH TLV-TWA	20 ppm
ACGIH TLV-STEL	NO INFO
OSHA PEL-TWA	50 ppm
COMPANY	N.E.
LD50(ORAL)	636 mg/kg (rat)
LD50(DERMAL)	14124 mg/kg (rabbit)
LC50	7523 mg/m3 (mouse)

OTHER LIMITS:
Prop 65-Developmental-01/01/91 EINECS 203-625-9

****

This product contains one or more reported carcinogens or suspected carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits recommended column.

****
****

This substance is classified as a hazardous air pollutant.

****

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:
Harmful if inhaled.
Causes eye irritation.
Causes skin irritation.
Vapors irritating to eyes and respiratory tract.
Flammable liquid and vapor.

EYE:
May cause eye burns.

SKIN:
May cause skin irritation.
Prolonged contact with the skin can cause chemical burns.
Product contains a component which can be absorbed through the skin.
Excessive exposure may cause hemolysis (red blood cell damage) which can impair the blood's ability to transport oxygen.
Material may aggravate an existing dermatitis.

INHALATION:
Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.
Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.
Excessive inhalation of vapors can cause nasal and respiratory irritation.
Liquid or vapor may be irritating to skin, eyes, throat or lungs.
Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

INGESTION:
Moderately toxic. May cause stomach discomfort, nause, vomiting, diarrhea, and narcosis.
Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.
May cause nausea, vomiting and diarrhea.

CHRONIC EFFECTS:
Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:
Kidney damage

Eye damage
Lung damage
Liver damage
Spleen damage
Anemia
Brain damage

Chronic overexposure to a component or components is this product has been suggested as a cause of the following effects in humans:
Liver damage
Cardiac abnormalities

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Repeated breathing or skin contact of methyl ethyl ketone may increase the potency of neurotoxins such as hexane if exposures occur at the same time.

Central nervous system depression, shock, coma, visual disturbances, and death. Onset of symptoms may be delayed as long as 30 hours.

Rats exposed to titanium dioxide dust at 250 mg/m3 developed lung cancer, however, such exposure levels are not attainable in the workplace with this material.

Product contains toluene which may be harmful to the fetus based on animal studies.

Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

In February 2000 the International Agency for Research on Cancer (IARC) classified ethylbenzene as possibly carcinogenic to humans (Group 2B) on the basis of sufficient evidence for carcinogenicity in experimental animals but inadequate evidence for cancer in humans.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

Flush with large quantities of water for 15 minutes.

SKIN CONTACT:

Wash with soap and water. Get medical attention if irritation develops or persists.

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

Ingestion of large quantities of this material will result in methanol poisoning. In this case treatment should include hemodialysis; the administration of ethanol to interfere with the metabolism of methanol and the administration of sodium carbonate to correct acidosis.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint . . . . . : 25.0 øF
Explosion Level . . . . . : Low (LEL) - .8
High (UEL)- 13.1

EXTINGUISHING MEDIA:
Use Dry Chemical, Carbon Dioxide or Chemical Foam.
FIRE-FIGHTING PROCEDURES AND EQUIPMENT:
Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat.
Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back.
Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used.
Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP AND CONTAINMENT:
Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire.
Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

SECTION 7 - HANDLING AND STORAGE

HANDLING:
Wash hands thoroughly after handling.
This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:
Warning! This product contains a chemical or chemicals known to the State of California to cause cancer.
STORAGE:
Store in a cool dry area with ventilation suitable for storing materials shown in section 2.
Keep away from heat, sparks and flame.
Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:
Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.
RESPIRATORY PROTECTION:
If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.
SKIN PROTECTION:
Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.
EYE PROTECTION:
Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.
OTHER PROTECTIVE EQUIPMENT:
Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.
HYGIENIC PRACTICES:
Wash hands before eating or smoking. Smoke in designated areas only.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure	85.00 mm Hg @ 20 C
Vapor Density	3.70
Boiling Range	Lower - 175.0 øF
	Higher - 302.0 øF
Specific Gravity	1.085
Formula Weight per Volume	9.0323 LB/GL
VOC (Calculated, LB/GAL)	5.272
VOC (Calculated, GM/L)	631.74
Percent Volatile by Weight	57.2061
Percent Volatile by Volume	71.1215
Evaporation Rate	4.600 (n-Butyl Acetate = 1)
Viscosity	-N/A

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:
Avoid contact with heat, sparks, and open flame.

INCOMPATIBILITIES:
Strong oxidizing agents.

DECOMPOSITION:
Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

POLYMERIZATION:
No hazardous polymerization will occur under normal conditions.

STABILITY:
The product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:
Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:
CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:
PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II
(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:
CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL
(Regulatory sources: IATA Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL
(Regulatory sources: IATA Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:
This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

ETHYLBENZENE
CAS# 100-41-4 PCT BY WT: .6100

XYLENE
CAS# 1330-20-7 PCT BY WT: 2.8110

TOLUENE
CAS# 108-88-3 PCT BY WT: 21.5560

FEDERAL REGULATIONS:
TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:
This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:
Warning! This product contains a chemical or chemicals known to the State of California to cause cancer.
Warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW
The following non-hazardous ingredients are among the top five components in this product

CHEMICAL NAME	CAS NUMBER

PENNSYLVANIA RIGHT-TO-KNOW
The following non-hazardous ingredients are present in the product at greater than 3 %

CHEMICAL NAME	CAS NUMBER
Acrylic Polymer	Not Listed
Cellulose Acetate Butyrate	9004-36-8

INTERNATIONAL REGULATIONS:
CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.
HMIS RATINGS:
HEALTH: 2* FLAMMABILITY: 3 REACTIVITY: 0 PERSONAL PROTECTION: B